

IN THE CLAIMS

Please amend Claims 1, 14, 26, and 29 as indicated.

Please cancel Claims 39-49 without prejudice and without disclaimer of subject matter.

1. (Currently Amended) A computer program product including an optical service agent stored on a non-transitory computer-readable medium for managing communication services for a user in an optical communication system in which the user lacks at least some network information related to the services, comprising:

a user-to-network interface (UNI) for interfacing with an optical communication network, including signaling to a network device having network information related [[,]] to the communication services, including network topological information, to cause the network device to signal an indication of group membership to other devices in communication with the optical communication network; and

optical service logic for obtaining a new optical communication path from the optical communication network via the network device by signaling through the UNI, the network device selecting the communication path based at least in-part on user network or application requirements and the network information related to the communication services and managing said optical communication path for the user without exposing the network topological information to the user,

whereby the user need not have the network topological information in order to obtain a new optical communication path.

2. (Previously Presented) The computer program product of claim 1, wherein the optical communication network comprises an automatically switched optical/transport network (ASON), and wherein the UNI comprises an ASON UNI.

3. (Previously Presented) The computer program product of claim 1, further comprising auto-discovery logic for automatically discovering peer users.

4. (Previously Presented) The computer program product of claim 3, wherein the auto-discovery logic comprises an advertisement mechanism for sending and receiving peer information.

5. (Previously Presented) The computer program product of claim 4, further comprising a peer database for storing peer information.

6. (Previously Presented) The computer program product of claim 1, further comprising peer authentication logic for authenticating peer users.

7. (Previously Presented) The computer program product of claim 1, further comprising peer-to-peer signaling logic for communicating with peer users.

8. (Previously Presented) The computer program product of claim 7, wherein the optical service logic coordinates communication services with peer users via the peer-to-peer signaling logic.

9. (Previously Presented) The computer program product of claim 1, wherein the optical service agent comprises an application component and a network component.

10. (Previously Presented) The computer program product of claim 9, wherein the application component and the network component are situated within the user, and wherein the network component implements the UNI for interfacing with the optical communication network.

11. (Previously Presented) The computer program product of claim 9, wherein the application component is situated within the user and the network component is situated within the optical communication network, and wherein the application component and the network component communicate via the UNI.

12. (Previously Presented) The computer program product of claim 9, wherein the application component and the network component communicate via a control interface, and wherein the network component interfaces with the optical communication network via the UNI as a proxy for the application component.

13. (Previously Presented) The computer program product of claim 1, further comprising an application program interface (API) for interfacing with a user application.

14. (Currently Amended) A device comprising:

a user application stored on a non-transitory computer-readable medium and executable by a computer, the user application requiring a new communication path from an optical communication network; and

an optical service agent stored on a non-transitory computer-readable medium and executable by a computer, the optical service agent for obtaining the new optical communication path from a network device associated with the optical communication network via a user-to-network interface (UNI), the network device being operable to manage said optical communication path for the user application and including network information related to communication paths, including network topological information, and optical service logic for obtaining new optical communication paths from the optical communication network in response to signaling from the optical service agent via the UNI based at least in-part on user network or application requirements and the network information related to the communication paths, and without exposing the network topological information to the user, whereby the user need not have the network topological information in order to obtain a new optical communication path.

15. (Original) The device of claim 14, wherein the optical communication network comprises an automatically switched optical/transport network (ASON), and wherein the UNI comprises an ASON UNI.

16. (Original) The device of claim 14, wherein the optical service agent comprises auto-discovery logic for automatically discovering peer users.

17. (Original) The device of claim 16, wherein the auto-discovery logic comprises an advertisement mechanism for sending and receiving peer information.

18. (Original) The device of claim 14, wherein the optical service agent comprises a peer database for storing peer information.

19. (Original) The device of claim 14, wherein the optical service agent comprises peer authentication logic for authenticating peer users.

20. (Original) The device of claim 14, wherein the optical service agent comprises peer-to-peer signaling logic for communicating with peer users.

21. (Original) The device of claim 20, wherein the optical service agent coordinates communication services with peer users via the peer-to-peer signaling logic.

22. (Original) The device of claim 14, wherein the optical service agent comprises an application component and a network component, and wherein the network component implements the UNI for interfacing with the optical communication network.

23. (Original) The device of claim 14, wherein the optical service agent comprises an application component that communicates with a peer network component in the optical communication network via the UNI.

24. (Original) The device of claim 14, wherein the optical service agent comprises an application component that communicates with a network component via a control interface, and wherein the network component interfaces with the optical communication network via the UNI as a proxy for the application component.

25. (Original) The device of claim 14, wherein the optical service agent comprises an application program interface (API) for interfacing with the user application.

26. (Currently Amended) Apparatus for use in optical communication network, comprising:

a controller for providing optical communication services: and
an optical service agent stored on a non-transitory computer-readable medium and executable by a computer, the optical service agent for obtaining a new optical communication path from the controller, wherein the controller is operable to manage said optical communication path for a network user and includes network information related to communication paths, including network topological information, and wherein the controller is operable in response to signaling from the optical service agent to obtain new optical

communication paths from the optical communication network based at least in-part on user network or application requirements and the network information related to the communication paths, and without exposing the network topological information to the user, whereby the user need not have the network topological information in order to obtain a new optical communication path.

27. (Previously Presented) The apparatus of claim 26, wherein the optical service agent implements a user-to-network interface (UNI) for interfacing with the controller.

28. (Previously Presented) The apparatus of claim 27, wherein the optical communication network comprises an automatically switched optical/transport network (ASON), and wherein the UNI comprises an ASON UNI.

29. (Currently Amended) A system comprising:
an optical communication network; and
a first network user coupled to the optical communication network, wherein the first network user comprises an optical service agent stored on a non-transitory computer-readable medium and executable by a computer, the optical service agent for obtaining new optical communication paths from the optical communication network via a network device through a user-to-network interface (UNI), the network device managing the optical communication paths for the first network user, and including network information related to communication paths, including network topological information, and optical service logic operable in response to

signaling from the optical service agent for obtaining new optical communication paths from the optical communication network based at least in-part on user network or application requirements and the network information related to the communication paths, and without exposing the network topological information to the user, whereby the user need not have the network topological information in order to obtain a new optical communication path.

30. (Original) The system of claim 29, wherein the optical communication network comprises an automatically switched optical/transport network (ASON), and wherein the UNI comprises an ASON UNI.

31. (Original) The system of claim 29, wherein the optical service agent comprises an application component and a network component, and the network component implements the UNI for interfacing with the optical communication network.

32. (Original) The system of claim 29, wherein the optical service agent comprises an application component and the optical communication network comprises network component, and wherein the application component and the network component communicate via the UNI.

33. (Original) The system of claim 29, further comprising a network component, wherein the optical service agent comprises an application component that communicates with the network component via a control interface, and wherein the network component interfaces with the optical communication network via the UNI as a proxy for the application component.

34. (Original) The system of claim 29, further comprising a second network user coupled to the optical communication network, said second network user comprising a second optical service agent.

35. (Original) The system of claim 34, wherein each of said optical service agents comprises auto-discovery logic for automatically discovering the other of said optical service agents.

36. (Original) The system of claim 34, wherein each of said optical service agents comprises peer authentication logic for authenticating the other of said optical service agents.

37. (Original) The system of claim 34, wherein each of said optical service agents comprises peer-to-peer signaling logic for coordinating communication services with the other of said optical service agents.

38. (Original) The system of claim 29, further comprising a second network user coupled to the optical communication network, said second network user excluding an optical service agent.

39.-49. (Cancelled)